


REED RESORT (110 lbs.)

Eight 60" Reed trunks, forty-six 60" limbs, four 8" couplers, thirty-two 1" screws



1. Insert eight limbs in one trunk, leaving 4" of limb through one side of trunk.
2. Lay trunk down on its side, with group of five limbs touching the ground and group of three limbs facing vertical.
3. Take second trunk at an angle and insert onto the group of three vertical limbs, starting with the "V-shaped" slot on the bottom of trunk. Keep trunk as level as possible to ensure alignment of limb slots. Slide second trunk down within 20" of bottom trunk. Repeat for trunks three and four.
4. Repeat steps 1-3 with remaining trunks. **You should have two identical structures when step 4 is complete.**
5. Tilt identical structures where the trunks are parallel to the ground, with five limbs facing vertical. On one structure, secure four 8" Couplers to bottoms of the four trunks, using sixteen 1" screws, four screws per trunk.
6. Line up identical structures with "V-shaped" limb slots facing the same direction. Slide identical structure onto the couplers, ensuring that the trunks are touching. Secure remaining trunks to couplers with sixteen 1" screws, four screws per trunk.
7. Insert remaining limbs vertically, leaving 4" of limb through one side of trunk. Structure should sit level and parallel to the ground.
8. Weight by threading concrete block (not included) over two of the middle upright limbs. *See photo above right.*

